
	Bucket Wheel Specifications 60/80FS, 80/120FS, 150/200FS	
---	---	---

Model	60/80FS	80/120FS	150/200FS
Slurry (max)	1100 GPM	1660 GPM	2100 GPM
Solids (max)	140 TPH (127 MTPH)	210 TPH (190 MTPH)	350 TPH (317 MTPH)
Volume (Solids)	105 y ³ /h (80 m ³ /h)	155 y ³ /h (120 m ³ /h)	260 y ³ /h (200 m ³ /h)
Drive HP	5 HP	7.5 HP	10 hp
Weight (empty)	5.5 Tons (5 MT)	11.5 tons (10.4 MT)	17.5 Tons (16 MT)
Weight (operating)			
Wheel Dia.	11'9-3/4" (3600 mm)	14'9-1/8" (4500 mm)	16'2-7/8" (4950 mm)
Wheel Width	28-1/2" (722 mm)	28-1/2" (722 mm)	36-1/4" (922 mm)
Tank Length (O.A.)	14'6-1/2" (4432 mm)	23'4" (7110 mm)	25'5-1/8" (7750 mm)
Tank Width (O.A.)	8'6-3/8" (2600 mm)	9'6-1/8" (2900 mm)	11'1/4" (3360 mm)

Aggregate Technology

50 Rosemount Avenue, Port Colborne, ON, Canada L3K 5P7
tel.: (905) 834-3702; fax: (905) 834-0117